



*Specializing in Research & Development of High Performance Pressure Sensitive Tapes*

---

## Product Data Sheet DC-2125

**Product Description:** Product DC-2125 is a double coated tissue tape feature an acrylic adhesive system with excellent adhesion, holding power and initial tack. This product is suitable for high temperature flying splices on paper, film and foils up to and exceeding 400<sup>0</sup>F dependent on exposure time. Also ideal for laminating, mounting and name plate applications. The product can be supplied in a colorless version or a black tissue for identification of splice and ease of use.

Physical Characteristics	Nominal Values
Total Tape Thickness	7.0 mils
Carrier	Black Tissue
Adhesive Type	Solvent Acrylic
Chemical Resistance	Medium-High
Liner	White Paper Liner
Holding Power, 1"x1"x1000gms @ 250 <sup>0</sup> F	> 3hrs
180 degree Peel Adhesion to Stainless Steel	95 oz/in
Tape Color	Black or Colorless
Temperature Resistance (short term, sec/min)	-10F-400F
Standard Length	55 yds

**Tape Application:** To achieve ultimate bond strength please be sure materials being bonded are clean and free of dust, dirt, oil or other substances which can affect the bond of the tape adhesive. Firm application pressure will promote a strong, long lasting bond. Adhesive bond strength is dependent upon the material type being bonded. If a variety of materials are being used, please be sure to test the suitability of product performance with each material. Please contact Custom Adhesive Products at the phone number below with questions regarding your taping applications and needs.

---

**Notice:** Physical and performance values listed above are average values obtained from tests performed according to PSTC or ASTM standard test methods. Custom Adhesive Products does not make any warrant of any kind as to the results listed above. The information listed above does not represent a performance guarantee. Product performance may vary with each individual application and the purchaser should test the product prior to use and satisfy themselves regarding product functionality in their application. Custom Adhesive Products shall not be liable for damages in excess of the purchase price of its products or for incidental or consequential damages.

[www.customadhesiveproducts.com](http://www.customadhesiveproducts.com) 6610 Hillwood Ct Racine, WI 53403  
(P) 262-595-0568 Toll-Free: 800-440-8273 (F) 262-595-0566

Rev 7/06