

Specializing in Research & Development of High Performance Pressure Sensitive Tapes

Product Data Sheet Polyethylene Film Tapes

Product Description: Family of LDPE film tapes for various applications such as masking, wrapping, sealing, splicing, color coding, packaging, identification, etc.

Product	Thickness	Tensile	Elongation	Adhesion	Adhesive Type	Applications
SC-1200	5.5 mil	12 lb/in	500%	45 oz/in	2.0 mil Acrylic	Permanent pipe wrap, splicing, seaming, patching
SC-1201	4.7 mil	11.3 lb/in	300%	10 oz/in	Synthetic rubber	Removable protective masking, electroplate masking, color coding (Available black, red and green)
SC-1202	7.0 mil	18 lb/in	300%	60 oz/in	Synthetic Rubber	Wire identification, surface protection, seaming, splicing (Available clear, white, black or red)
SC-1203	7.0 mil	18 lb/in	80%	76oz/in	Synthetic Rubber	UV stabilized, masking of windows and doors in stucco applications (Available Red or white)
SC-1204	9.0 mil	25 lb/in	100%	70 oz/in	Synthetic Rubber	PE splicing, patching/reparing poly sheeting, packaging, etc. (Available clear, white, red, black, blue)

Tape Application

To achieve ultimate bond strength please be sure materials being bonded are clean and free of dust, dirt, oil or other substances which can effect the bond of the tape adhesive. Firm application pressure will promote a strong, long lasting bond. Adhesive bond strength is dependent upon the material type being bonded. If a variety of materials are being used, please be sure to test the suitability of product performance with each material. Please contact Custom Adhesive Products at the phone number below with questions regarding your taping applications and needs.

Revised: 2/07



Notice: Physical and performance values list above are average values obtained from tests performed according to PSTC or ASTM standard test methods. Custom Adhesive Products does not make any warrant of any kind as to the results listed above. The information listed above does not represent a performance guarantee. Product performance may vary with each individual application and the purchaser should test the product prior to use and satisfy themselves regarding product functionality in their application. Custom Adhesive Products shall not be liable for damages in excess of the purchase price of its products or for incidental or consequential damages.

Revised: 2/07