



*Specializing in Research & Development of High Performance Pressure Sensitive Tapes*

## Product Data Sheet SC-1262

**Product Description:** Product SC-1262 is a pure skived Teflon (PTFE) with silicone adhesive. Used in electrical applications such as harness/coil wraps & separators, transformers and slot liner where good insulation and heat resistance are required. Also used in mechanical applications such as heat sealing bars & jaws, labeling machine pressure pads, chute liners, anti-friction devices, bearings, forming dies, aircraft mold release & guide rails where high temperature, maximum slip and lubricity are required. SC-1262 is a high density, tensilized skived PTFE film which provides higher tensile strength, lower elongation and higher dielectric strength than regular skived film.

Physical Characteristics	Nominal Values
Total Tape Thickness	3.50 mils
Backing Thickness	2.00 mils
Adhesive Thickness	1.50 mils
Break Strength	30 lbs/in
Elongation	100 %
180 degree Peel Adhesion to Stainless Steel	25 oz/in
Tape Color	Brown
Temperature Resistance (short term, sec/min) (long term, days/weeks)	-100F to 500F
Standard Length	36 yards

**Tape Application:** To achieve ultimate bond strength please be sure materials being bonded are clean and free of dust, dirt, oil or other substances which can affect the bond of the tape adhesive. Firm application pressure will promote a strong, long lasting bond. Adhesive bond strength is dependent upon the material type being bonded. If a variety of materials are being used, please be sure to test the suitability of product performance with each material. Please contact Custom Adhesive Products at the phone number below with questions regarding your taping applications and needs.

**Notice:** Physical and performance values listed above are average values obtained from tests performed according to PSTC or ASTM standard test methods. Custom Adhesive Products does not make any warrant of any kind as to the results listed above. The information listed above does not represent a performance guarantee. Product performance may vary with each individual application and the purchaser should test the product prior to use and satisfy themselves regarding product functionality in their application. Custom Adhesive Products shall not be liable for damages in excess of the purchase price of its products or for incidental or consequential damages.

[www.customadhesiveproducts.com](http://www.customadhesiveproducts.com) 6610 Hillwood Ct Racine, WI 53403  
(P) 262-595-0568 Toll-Free: 800-440-8273 (F) 262-595-0566

Rev 7/06