



Specializing in Research & Development of High Performance Pressure Sensitive Tapes

Product Data Sheet

SC-4055

Product Description: Product SC-4055 is an extremely high tack silicone pressure sensitive splicing and masking tape. Constructed of a 1 mil conformable polyester backing, SC-4055 provides extremely good quick stick capability to silicone coated papers and films, ideal for splicing applications. High temperature resistance, clean removal and a conformable silicone adhesive make this product a good choice for specialty masking applications. Product is self-wound and pink in color.

| Physical Characteristics | Nominal Values |
|---|------------------------------|
| Total Tape Thickness | 2.50 mils |
| Backing Thickness | 1.00 mils |
| Adhesive Thickness | 1.50 mils |
| Tensile Strength | 27 lbs/in |
| Elongation | 100 % |
| 180 degree Peel Adhesion to Stainless Steel | 32 oz/in |
| Tape Color | Pink |
| Temperature Resistance (short term, sec/min) (long term, days/weeks) | -60F to 500F -60F to 300F |
| Standard Length | 72 yds |

Tape Application: To achieve ultimate bond strength please be sure materials being bonded are clean and free of dust, dirt, oil or other substances which can affect the bond of the tape adhesive. Firm application pressure will promote a strong, long lasting bond. Adhesive bond strength is dependent upon the material type being bonded. If a variety of materials are being used, please be sure to test the suitability of product performance with each material. Please contact Custom Adhesive Products at the phone number below with questions regarding your taping applications and needs.

Notice: Physical and performance values listed above are average values obtained from tests performed according to PSTC or ASTM standard test methods. Custom Adhesive Products does not make any warrant of any kind as to the results listed above. The information listed above does not represent a performance guarantee. Product performance may vary with each individual application and the purchaser should test the product prior to use and satisfy themselves regarding product functionality in their application. Custom Adhesive Products shall not be liable for damages in excess of the purchase price of its products or for incidental or consequential damages.

www.customadhesiveproducts.com 6610 Hillwood Ct Racine, WI 53403
(P) 262-595-0568 Toll-Free: 866-440-8273 (F) 262-595-0566

Rev 7/06